



e^N-CHECK 2500 CHECK READER



Model 2500

Quiet, efficient, and accurate. Three words that describe the most versatile check reader in the market today. Ingenico has used the experience we gained in becoming the global leader in check reading technology to bring you the eⁿ-Check 2500.

Ergonomically Designed for Flexibility and Simplicity

- The angle of the check entry area and intuitive design enhance ease-of-use
- Enhanced cable channeling allow the combined power/communications cable to be routed out the back or side of the eⁿ-Check 2500

Expressly Created for Superior Performance

- Improved recognition algorithms produce highly-accurate, first-pass reads
- 7-segment display provides detailed “bad check” information
- “Hand back/hold away” ensures that exception items are treated differently than accepted items
- Rapid read times enhance customer service

Specifically Built to Protect Your Investment

- Modular design allows users to add future options such as check trays for sorting and interface to PC hosts
- Automatically detects communication interfaces on power up
- Users can implement check conversion with or without the addition of image capture devices
- Optional magnetic stripe reader



BLM TECHNOLOGIES

Solutions you can bank on.

800 358 5574

www.blmtechnology.com



e^N-CHECK 2500 CHECK READER

Product Specifications:

MICR Fonts	E13B, CMC7, and CMC0
Optional Magstripe Reader	Dual or triple track, bi-directional
Average Track Speed	21 inches per second (533 mm per second)
User Display	7 segment readout and LED with 3 colors
Application Software	Preloaded
Programmability	Downloadable via platform, configuration checks or PC Field upgradeable firmware via flash ROM
Interfaces	IBM, NCR, Fujitsu/ICL, Symbol Tech., Verifone and most other POS, PC, wedge and terminal platforms
Protocols	RS232, RS485, TTL, Keyboard Wedge, OCIA, CORA, MDL and others
Life Expectancy	One million reads
Voltage	4.9 V DC to 16 V DC (maximum, including ripple)
Current	400 mA normal operations (average) 250 mA quiescent
External Power Supply	None required in most installations when at least 300 mA is available from the POS port
Dimensions & Weight	70.6 mm x 76.2 mm x 182.4 mm 380 g

CONTACT US TODAY:

BLM Technologies, Inc.
14755 27th Avenue North, Plymouth, MN 55447
800 358 5574
www.blmtechnology.com



©2008 BLM Technologies, Inc. All Rights Reserved

800 358 5574

www.blmtechnology.com